



**T/A** Denotes a Traction/Advantage Benefit

Tire Size	Serv. Desc.	Sidewall	MSPN	Stock #	Rim Width Range (inches)	*Section Width on Measuring Rim Width**	*Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load Single (lbs@psi)
LT215/75R15/C	100Q	RWL	71736	439-120	5.5 - 7.0	8.4 on 6.0	27.8	16.0	748	1765@50
LT235/75R15/C	104Q	RWL	73110	439-127	6.0 - 7.0	9.1 on 6.5	29.0	16.0	717	1985@50
LT325/60R15/C	106Q	RWL	41347	439-360	9.0 - 11.0	12.9 on 9.5	30.5	16.0	682	2095@35
LT215/70R16/C	100Q	RWL	81379	439-427	5.5 - 7.0	8.7 on 6.5	28.0	16.0	743	1765@50
LT225/70R16/C	102Q	RWL	78915	439-631	6.0 - 7.0	8.9 on 6.5	28.5	16.0	730	1875@50
LT225/75R16/D	110Q	RWL	45961	439-122	6.0 - 7.0	8.8 on 6.0	29.4	16.0	707	2335@65
LT235/70R16/C	104Q	RWL	92965	439-138	6.0 - 7.5	9.5 on 7.0	29.1	16.0	715	1985@50
LT235/85R16/E	120Q	RWL	41577	439-166	6.0 - 7.0	9.3 on 6.5	31.8	16.0	654	3042@80
LT245/70R16/D	113Q	RWL	56856	439-444	6.5 - 7.5	9.7 on 7.0	29.6	16.0	703	2535@65
LT245/75R16/E	120Q	RWL	84488	439-139	6.5 - 7.5	9.7 on 7.0	30.6	16.0	680	3042@80
LT255/70R16/D	115Q	RWL	53876	439-265	6.5 - 8.0	10.2 on 7.5	30.2	16.0	689	2680@65
LT265/70R16/D	117Q	RWL	41561	439-546	7.0 - 8.5	10.7 on 8.0	30.7	16.0	678	2835@65
LT265/75R16/D	120Q	RWL	43366	439-167	7.0 - 8.0	10.5 on 7.5	31.8	16.0	654	3042@65
LT275/70R16/D	119Q	RWL	56638	439-545	7.0 - 8.5	11.0 on 8.0	31.3	16.0	665	3000@65
LT285/75R16/D	122Q	RWL	56567	439-185	7.5 - 9.0	11.3 on 8.0	32.9	17.0	632	3305@65
LT295/75R16/D	123Q	RWL	96547	439-454	7.5 - 9.5	11.6 on 8.0	33.5	17.0	621	3415@65
LT315/75R16/D	121Q	RWL	95328	439-322	8.0 - 10.0	12.1 on 8.5	34.7	17.0	599	3195@50
LT265/70R17/C	112Q	RWL	46621	439-446	7.0 - 8.5	10.7 on 8.0	31.8	16.0	654	2470@50
27x8.50R14LT/C	95Q	RWL	90127	439-825	6.0 - 7.5	8.5 on 7.0	26.6	16.0	782	1515@50
30x9.50R15LT/C	104Q	RWL	50534	439-890	6.5 - 8.5	9.4 on 7.5	29.5	16.0	705	1990@50
31x10.50R15LT/C	109Q	RWL	60316	439-895	7.0 - 9.0	10.5 on 8.5	30.7	16.5	677	2250@50
32x11.50R15LT/C	113Q	RWL	87811	439-924	8.0 - 10.0	11.4 on 9.0	31.7	17.0	656	2530@50
33x9.50R15LT/C	113Q	RWL	95155	439-938	6.5 - 8.5	9.5 on 7.5	32.7	16.0	636	2510@50
33x10.50R15LT/C	114Q	RWL	75595	439-905	7.0 - 9.0	10.6 on 8.5	32.7	16.0	636	2620@50
33x12.50R15LT/C	108Q	RWL	75406	439-943	8.5 - 11.0	12.4 on 10.0	32.7	17.0	636	2225@35
35x12.50R15LT/C	113Q	RWL	95210	439-972	8.5 - 11.0	12.7 on 10.0	34.7	17.0	599	2555@35
31x10.50R16.5LT/D	116Q	RWL	77809	439-898	8.25 only	10.5 on 8.25	30.7	16.5	678	2745@65
33x12.50R16.5LT/D	118Q	RWL	54758	439-947	8.25 - 10.50	12.3 on 9.75	32.7	17.0	634	2930@50
35x12.50R16.5LT/D	123Q	RWL	55633	439-974	8.25 - 10.50	12.5 on 9.75	34.7	17.0	600	3385@50
37x12.50R17/D	124Q	RWL	99249	439-481	8.5 - 11.0	12.8 on 10.0	36.3	17.0	574	3525@50

\*The dimensions shown are average values for tires measured on the measuring rim width. Individual tires may vary from data shown.

\*\*Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

#DANGER: Never mount a 16" diameter tire on a 16.5" rim.

#WARNING: Serious or fatal injury may result from: Tire failure due to underinflation/overloading -- follow owner's manual or Tire Information Placard in vehicle. Explosion of tire/rim assembly due to improper mounting. Never inflate beyond 40 psi to seat beads. Only specially trained persons should mount tires. Mixing bias tires with radials on the same vehicle. Mixing different tire sizes. Follow manufacturer's recommendations.

††Compared to Radial All-Terrain T/A®.

Estimated data subject to change for all sizes.

Adventure Assurance Program for All-Terrain T/A<sup>®</sup> KO tires. If you get stuck, we'll send a truck: the first roadside assistance coupled with a manufacturer's off-road assistance program. It's your assurance that help is at hand 24 hours a day, 365 days a year for a period of 24 months from the date of purchase.

